



# UNITED STATES PATENT AND TRADEMARK OFFICE

*eeu*

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/091,638	03/05/2002	Richard A. Bardini	SONY-16000	9147

28960 7590 08/29/2007  
HAVERSTOCK & OWENS LLP  
162 N WOLFE ROAD  
SUNNYVALE, CA 94086

EXAMINER
----------

PATEL, CHANDRAHAS B

ART UNIT	PAPER NUMBER
----------	--------------

2616

MAIL DATE	DELIVERY MODE
-----------	---------------

08/29/2007

PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	Application No. 10/091,638	Applicant(s) BARDINI ET AL.	
	Examiner Chandras Patel	Art Unit 2616	

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --**

**Period for Reply**

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.138(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 20 June 2007.
- 2a) ☐ This action is FINAL.                      2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-61 is/are pending in the application.
- 4a) Of the above claim(s) 1-4, 6, 8-11, 18, 21, 25-27, 31, 34-37 and 43-46 is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 5, 7, 12-17, 19, 20, 22-24, 28-30, 32, 33, 38-42 and 47-61 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 05 March 2002 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \* c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- |  |   |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)                                | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948)                       | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____  |

## DETAILED ACTION

### *Claim Rejections - 35 USC § 102*

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

2. Claims 5, 20, 22, 29, 30, 50-61 are rejected under 35 U.S.C. 102(e) as being anticipated by Ghodrat et al. (USPN 6,717,947).

**Regarding claim 5**, Ghodrat teaches a method of performing retransmission and flow control comprising **[Abstract]**: a. configuring a back channel between a transmitting device and a receiving device for providing retransmission and flow control information from the receiving device to the transmitting device related to a stream of isochronous data packets transmitted from the transmitting device to the source device **[Col. 5, lines 18-20]**; b. monitoring the stream of isochronous data packets received at the receiving device for necessary retransmission or flow control **[Col. 6, lines 16-19]**; c. configuring a back channel packet for indicating a retransmission or flow control function to perform, wherein the back channel packet includes a control instruction that instructs the transmitting device to reset transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets, and further wherein the back channel packet includes a dbc field that identifies the specific packet within the stream of isochronous data packets **[Col. 7, lines 36-53, 65-67, – Col. 8, lines 1-9, sequence number field identified the specified packet from the stream of data**

Art Unit: 2616

packets]; and d. transmitting the back channel packet from the receiving device to the transmitting device over the back channel [Col. 7, lines 36-41].

**Regarding claim 20**, Ghodrat teaches a method of transmitting flow control and retransmission information [Abstract] comprising: a. configuring a transmitting plug on a receiving device for transmitting an isochronous back channel packet over an isochronous channel via the transmitting plug to a transmitting device [Col. 5, lines 33-39]; b. determining flow control and retransmission information based on the status of a received isochronous data packet at the receiving device, wherein the received isochronous data packet is one of a stream of isochronous data packets transmitted from the transmitting device to the receiving device, wherein the stream of isochronous data packets is transmitted in non real-time [Fig. 3, 210, Col. 5, lines 40-41, **asynchronous communication is done in non real-time**]; c. packetizing flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; and d. transmitting the isochronous back channel packet from the receiving device over the isochronous back channel via the transmitting plug [Col. 7, lines 36-41].

**Regarding claim 22**, Ghodrat teaches the status of the received isochronous data packet indicates a packet transmission error and instructs the transmitting device to reset transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets [Col. 7, lines 36-53, 65-67, – Col. 8, lines 1-9, **sequence number field identified the specified packet from the stream of data packets**].

**Regarding claim 29**, Ghodrat teaches a method of receiving flow control and retransmission information [Abstract] comprising: a. configuring a receiving plug on a transmitting device for receiving an isochronous back channel packet from a receiving device,

wherein the isochronous back channel packet is received over an isochronous channel via the receiving plug [Col. 5, lines 33-39]; b. receiving the isochronous back channel packet via the receiving plug [Col. 6, lines 16-19]; c. reading flow control and retransmission information included within the isochronous back channel packet wherein the flow control and retransmission information relates to a stream of isochronous data packets transmitted from the transmitting device to the receiving device and provides a control instruction to the transmitting device to regulate transmission of the stream of isochronous data packets [Fig. 3, 210]; and regulating transmission of the stream of isochronous data packets as determined by the control instruction, wherein the stream of isochronous data packets is transmitted in non real-time [Fig. 3, 210, Col. 5, lines 40-41, **asynchronous communication is done in non real-time**].

**Regarding claim 30**, Ghodrat teaches a method of configuring a plug to support an isochronous back channel [Col. 5, lines 18-39] comprising: a. embedding a back channel flow control information block within a plug configuration information block, wherein the back channel flow control information block is embedded within a non real-time plug transfer information block which is embedded within the plug configuration information block [Col. 5, lines 33-41, **IEEE 1394 is the plug and asynchronous communication is non real-time**]; b. defining a back channel information type within the back channel flow control information block, wherein the back channel information type indicates an isochronous back channel control mechanism for providing a flow control and retransmission control instruction [Fig. 3]; and c. setting an isochronous channel number field within the back channel flow control information block to indicate the isochronous channel used to send an isochronous back channel packet,

wherein the isochronous back channel packet includes the control instruction which is used to regulate a transmission of a stream of isochronous data packets [Col. 5, lines 55-67].

**Regarding claim 50**, Ghodrat teaches a method of performing retransmission and flow control [Abstract] comprising: a. configuring an isochronous channel between a transmitting device and a receiving device as an isochronous back channel for providing retransmission and flow control information from the receiving device to the transmitting device related to a stream of isochronous data packets transmitted from the transmitting device to the source device, wherein the stream of isochronous data packets is transmitted in non real-time [Col. 5, lines 18-20, Col. 5, lines 40-41, asynchronous communication is done in non real-time]; b. monitoring the stream of isochronous data packets received at the receiving device for necessary retransmission or flow control [Col. 6, lines 16-19]; c. configuring an isochronous back channel packet for indicating a retransmission or flow control function to perform [Fig. 3, 210]; and d. transmitting the isochronous back channel packet from the receiving device to the transmitting device over the isochronous back channel [Col. 7, lines 36-41].

**Regarding claim 51**, Ghodrat teaches a method of performing retransmission and flow control comprising [Abstract]: a. configuring an isochronous back channel between a transmitting device and a receiving device as an isochronous back channel for providing retransmission and flow control information from the receiving device to the transmitting device related to a stream of isochronous data packets transmitted from the transmitting device to the source device [Col. 5, lines 18-20]; b. monitoring the stream of isochronous data packets received at the receiving device for necessary retransmission or flow control [Col. 6, lines 16-19]; c. configuring an isochronous back channel packet for indicating a retransmission or flow

Art Unit: 2616

control function to perform **[Fig. 3, 210]**; d. transmitting the isochronous back channel packet from the receiving device to the transmitting device over the isochronous back channel, wherein the isochronous back channel packet includes a control instruction that instructs the transmitting device to reset transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets and a dbc field that identifies the specific packet within the stream of isochronous data packets **[Col. 7, lines 36-53, 65-67, – Col. 8, lines 1-9, sequence number field identified the specified packet from the stream of data packets]**.

**Regarding claim 52**, Ghodrat teaches an apparatus for communicating flow control and retransmission information **[Fig. 1]** comprising: a. a configuring circuit to configure a plug to communicate an isochronous back channel packet over an isochronous back channel **[Col. 5, lines 33-39]**; b. a packetizing circuit to packetize flow control and retransmission information within the isochronous back channel packet **[Col. 5, lines 61-63]**; c. a transceiver circuit configured to communicate the isochronous back channel packet via the plug **[Fig. 1, 25]**; d. a de-packetizing circuit to extract the flow control and retransmission information from the isochronous back channel packet **[Col. 7, lines 43-49]**; and e. a controller coupled to the configuring circuit, the packetizing circuit, the transceiver circuit, and the de-packetizing circuit to determine a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and apply the control instruction to the determined stream of isochronous data packets, wherein the stream of isochronous data packets is transmitted in non real-time **[Col. 7, lines 65-67 – Col. 8, lines 1-9, Col. 5, lines 40-41, asynchronous communication is done in non real-time]**.

**Regarding claim 53**, Ghodrat teaches an apparatus for communicating flow control and retransmission information **[Fig. 1]** comprising: a. a configuring circuit to configure a plug to communicate an isochronous back channel packet over an isochronous back channel **[Col. 5, lines 33-39]**; b. a packetizing circuit to packetize flow control and retransmission information within the isochronous back channel packet **[Col. 5, lines 61-63]**; c. a transceiver circuit configured to communicate the isochronous back channel packet via the plug **[Fig. 1, 25]**; d. a de-packetizing circuit to extract the flow control and retransmission information from the isochronous back channel packet **[Col. 7, lines 43-49]**; and e. a controller coupled to the configuring circuit, the packetizing circuit, the transceiver circuit, and the de-packetizing circuit to determine a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and apply the control instruction to the determined stream of isochronous data packets, wherein the control instruction is an indication to reset transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets, and further wherein the isochronous back channel packet includes a dbc field that identifies the specific packet within the stream of isochronous data packets **[Col. 7, lines 36-53, 65-67, – Col. 8, lines 1-9, sequence number field identified the specified packet from the stream of data packets]**.

**Regarding claims 54, 59**, Ghodrat teaches the isochronous back channel packet includes a control field that contains a value corresponding to the control instruction **[Col. 7, lines 36-41, retry packet contains the instruction]**.

**Regarding claim 55**, Ghodrat teaches an apparatus for communicating flow control and retransmission information **[Fig. 1]** comprising: a. a configuring circuit to configure a plug to



Art Unit: 2616

transmit an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. a packetizing circuit to packetize flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; c. a transceiver circuit configured to transmit the isochronous back channel packet via the plug, wherein the transceiver circuit is configured to transmit isochronous data packets in non real-time via the plug [Fig. 1, 25, Col. 5, lines 40-41, **asynchronous communication is done in non real-time**]; d. a de-packetizing circuit to extract the flow control and retransmission information from the isochronous back channel packet [Col. 7, lines 43-49]; and e. a controller coupled to the configuring circuit, the packetizing circuit, the transceiver circuit, and the de-packetizing circuit to determine a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and apply the control instruction to the determined stream of isochronous data packets [Col. 7, lines 65-67 – Col. 8, lines 1-9].

**Regarding claim 56,** Ghodrat teaches an apparatus for communicating flow control and retransmission information [Fig. 1] comprising: a. a configuring circuit to configure a plug to receive an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. a packetizing circuit to packetize flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; c. a transceiver circuit configured to receive the isochronous back channel packet via the plug, wherein the transceiver circuit is configured to receive isochronous data packets in non real-time via the plug [Fig. 1, 25, Col. 5, lines 40-41, **asynchronous communication is done in non real-time**]; d. a de-packetizing circuit to extract the flow control and retransmission information from the isochronous back channel packet [Col. 7, lines 43-49]; and e. a controller coupled to the configuring circuit, the

Art Unit: 2616

packetizing circuit, the transceiver circuit, and the de-packetizing circuit to determine a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and apply the control instruction to the determined stream of isochronous data packets [Col. 7, lines 65-67 – Col. 8, lines 1-9].

**Regarding claim 57**, Ghodrat teaches an apparatus for communicating flow control and retransmission information [Fig. 1] comprising: a. means for configuring a plug to communicate an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. means for packetizing flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; c. means for communicating the isochronous back channel packet via the plug [Fig. 1, 25]; d. means for extracting the flow control and retransmission information from the isochronous back channel packet [Col. 7, lines 43-49]; and e. means for controlling coupled to the means for configuring, the means for packetizing, the means for communicating, and the means for de-packetizing, wherein the means for controlling determines a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and applies the control instruction to the determined stream of isochronous data packets, wherein the stream of isochronous data packets is transmitted in non real-time [Col. 7, lines 65-67 – Col. 8, lines 1-9, Col. 5, lines 40-41, asynchronous communication is done in non real-time].

**Regarding claim 58**, Ghodrat teaches an apparatus for communicating flow control and retransmission information [Fig. 1] comprising: a. means for configuring a plug to communicate an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. means for packetizing flow control and retransmission information within the isochronous back

channel packet [Col. 5, lines 61-63]; c. means for communicating the isochronous back channel packet via the plug [Fig. 1, 25]; d. means for extracting the flow control and retransmission information from the isochronous back channel packet [Col. 7, lines 43-49]; and e. means for controlling coupled to the means for configuring, the means for packetizing, the means for communicating, and the means for de-packetizing, wherein the means for controlling determines a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and applies the control instruction to the determined stream of isochronous data packets, wherein the control instruction is an indication to reset transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets and further wherein the isochronous back channel packet includes a dbc field that identifies the specific packet within the stream of isochronous data packets [Col. 7, lines 36-53, 65-67, – Col. 8, lines 1-9, **sequence number field identified the specified packet from the stream of data packets**].

**Regarding claim 60**, Ghodrat teaches an apparatus for communicating flow control and retransmission information [Fig. 1] comprising: a. means for configuring a plug to transmit an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. means for packetizing flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; c. means for communicating the isochronous back channel packet via the plug, wherein the means for communicating is configured to transmit isochronous data packets in non real-time via the plug [Fig. 1, 25, Col. 5, lines 40-41, **asynchronous communication is done in non real-time**]; d. means for extracting the flow control and retransmission information from the isochronous back channel packet [Col. 7, lines 43-49]; and

Art Unit: 2616

e. means for controlling coupled to the means for configuring, the means for packetizing, the means for communicating, and the means for de-packetizing, wherein the means for controlling determines a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and applies the control instruction to the determined stream of isochronous data packets [Col. 7, lines 65-67 – Col. 8, lines 1-9].

**Regarding claim 61**, Ghodrat teaches an apparatus for communicating flow control and retransmission information [Fig. 1] comprising: a. means for configuring a plug to receive an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. means for packetizing flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; c. means for communicating the isochronous back channel packet via the plug, wherein the means for communicating is configured to receive isochronous data packets in non real-time via the plug [Fig. 1, 25, Col. 5, lines 40-41, **asynchronous communication is done in non real-time**]; d. means for extracting the flow control and retransmission information from the isochronous back channel packet [Col. 7, lines 43-49]; and e. means for controlling coupled to the means for configuring, the means for packetizing, the means for communicating, and the means for de-packetizing, wherein the means for controlling determines a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and applies the control instruction to the determined stream of isochronous data packets [Col. 7, lines 65-67 – Col. 8, lines 1-9].

***Claim Rejections - 35 USC § 103***

3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

4. Claims 7, 12-17, 19, 23, 24, 28, 32, 33, 38-42, 47-49 are rejected under 35 U.S.C. 103(a) as being unpatentable over Ghodrat et al. (USPN 6,717,947) in view of Dejanovic et al. (USPN 7,046,627).

**Regarding claim 7**, Ghodrat teaches a method of performing retransmission and flow control comprising **[Abstract]**: a. configuring a back channel between a transmitting device and a receiving device for providing retransmission and flow control information from the receiving device to the transmitting device related to a stream of isochronous data packets transmitted from the transmitting device to the source device **[Col. 5, lines 18-20]**; b. monitoring the stream of isochronous data packets received at the receiving device for necessary retransmission or flow control **[Col. 6, lines 16-19]**; c. configuring a back channel packet for indicating a retransmission or flow control function to perform **[Fig. 3, 210]**; d. transmitting the back channel packet from the receiving device to the transmitting device over the back channel **[Col. 7, lines 36-41]**.

However, Ghodrat does not teach the back channel packet includes a control instruction that instructs the transmitting device to stop transmitting the stream of isochronous data packets.

Dejanovic teaches the back channel packet includes a control instruction that instructs the transmitting device to stop transmitting the stream of isochronous data packets **[Col. 9, lines 40-42, 58-64, lines 58-64 teach the control instruction is sent through back channel]**.

It would have been obvious to one of ordinary skill in the art at the time the invention was made to stop transmitting data packets if congestion occurs [Col. 9, lines 40-42].

**Regarding claim 12**, Ghodrat teaches a method of performing retransmission and flow control comprising [Abstract]: a. configuring an isochronous back channel between a transmitting device and a receiving device as an isochronous back channel for providing retransmission and flow control information from the receiving device to the transmitting device related to a stream of isochronous data packets transmitted from the transmitting device to the source device [Col. 5, lines 18-20]; b. monitoring the stream of isochronous data packets received at the receiving device for necessary retransmission or flow control [Col. 6, lines 16-19]; c. configuring an isochronous back channel packet for indicating a retransmission or flow control function to perform [Fig. 3, 210]; d. transmitting the isochronous back channel packet from the receiving device to the transmitting device over the isochronous back channel [Col. 7, lines 36-41].

However, Ghodrat does not teach the back channel packet includes a control instruction that instructs the transmitting device to stop transmitting the stream of isochronous data packets.

Dejanovic teaches the back channel packet includes a control instruction that instructs the transmitting device to stop transmitting the stream of isochronous data packets [Col. 9, lines 40-42, 58-64, lines 58-64 teach the control instruction is sent through back channel].

It would have been obvious to one of ordinary skill in the art at the time the invention was made to stop transmitting data packets if congestion occurs [Col. 9, lines 40-42].

**Regarding claim 13**, Ghodrat teaches configuring a transmitting plug on the receiving device for transmitting the isochronous back channel packet over the isochronous back channel

Art Unit: 2616

and configuring a receiving plug on the transmitting device for receiving the isochronous back channel packet over the isochronous back channel [Col. 5, lines 33-39, IEEE 1394 is isochronous bus where 40 is configured to bidirectional communication].

Regarding claims 14, 33, 42, Ghodrat teaches the stream of isochronous data packets is transmitted in non real-time [Col. 5, lines 40-41, asynchronous communication is not done in real-time].

Regarding claim 15, Ghodrat teaches the isochronous back channel packet includes a control instruction that instructs the transmitting device to reset transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets [Col. 7, lines 36-53, 65-67, – Col. 8, lines 1-9, sequence number field identified the specified packet from the stream of data packets].

Regarding claim 16, Ghodrat teaches the isochronous back channel packet includes a dbc field that identifies the specific packet within the stream of isochronous data packets [Col. 7, lines 36-43, sequence number field identifies the packet].

Regarding claim 17, Ghodrat teaches the isochronous back channel packet includes a control field that contains a value corresponding to the control instruction [Col. 7, lines 36-41, retry packet contains the instruction].

Regarding claims 19, 38, 47, Ghodrat teaches the stream of isochronous data packets include audio/visual content data [Col. 2, lines 22-29, 38-39].

Regarding claim 23, Ghodrat teaches a method of transmitting flow control and retransmission information [Abstract] comprising: a. configuring a transmitting plug on a receiving device for transmitting an isochronous back channel packet over an isochronous

Art Unit: 2616

channel via the transmitting plug to a transmitting device [Col. 5, lines 33-39]; b. determining flow control and retransmission information based on the status of a received isochronous data packet at the receiving device, wherein the received isochronous data packet is one of a stream of isochronous data packets transmitted from the transmitting device to the receiving device, [Fig. 3, 210]; c. packetizing flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; and d. transmitting the isochronous back channel packet from the receiving device over the isochronous back channel via the transmitting plug [Col. 7, lines 36-41].

However, Ghodrat does not teach the status of the received isochronous data packet indicates the receiving device is not capable of receiving the stream of isochronous data packets and instructs the transmitting device to stop transmitting the stream of isochronous data packets.

Dejanovic teaches the status of the received isochronous data packet indicates the receiving device is not capable of receiving the stream of isochronous data packets and instructs the transmitting device to stop transmitting the stream of isochronous data packets [Col. 9, lines 40-42, 58-64, lines 58-64 teach the received data packet indicates about receiving device].

It would have been obvious to one of ordinary skill in the art at the time the invention was made to stop transmitting data packets if congestion occurs [Col. 9, lines 40-42].

**Regarding claim 24**, Ghodrat teaches a method of transmitting flow control and retransmission information [Abstract] comprising: a. configuring a transmitting plug on a receiving device for transmitting an isochronous back channel packet over an isochronous channel via the transmitting plug to a transmitting device [Col. 5, lines 33-39]; b. determining flow control and retransmission information based on the status of a received isochronous data



Art Unit: 2616

packet at the receiving device, wherein the received isochronous data packet is one of a stream of isochronous data packets transmitted from the transmitting device to the receiving device [Fig. 3, 210]; c. packetizing flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; and d. transmitting the isochronous back channel packet from the receiving device over the isochronous back channel via the transmitting plug [Col. 7, lines 36-41].

However, Ghodrat does not teach the status of the received isochronous data packet indicates that the receiving device is capable of resuming reception of the stream of isochronous data packets and instructs the transmitting device to restart transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets.

Dejanovic teaches the status of the received isochronous data packet indicates that the receiving device is capable of resuming reception of the stream of isochronous data packets and instructs the transmitting device to restart transmission of the stream of isochronous data packets starting from a specified packet within the stream of isochronous data packets [Col. 13, lines 49-54].

It would have been obvious to one of ordinary skill in the art at the time the invention was made to start from a specified a packet from the stream so that a view of traffic condition can be efficiently produced [Col. 6, lines 13-20].

**Regarding claim 28**, Ghodrat teaches a method of receiving flow control and retransmission information [Abstract] comprising: a. configuring a receiving plug on a transmitting device for receiving an isochronous back channel packet from a receiving device,

wherein the isochronous back channel packet is received over an isochronous channel via the receiving plug [Col. 5, lines 33-39]; b. receiving the isochronous back channel packet via the receiving plug [Col. 6, lines 16-19]; c. reading flow control and retransmission information included within the isochronous back channel packet wherein the flow control and retransmission information relates to a stream of isochronous data packets transmitted from the transmitting device to the receiving device and provides a control instruction to the transmitting device to regulate transmission of the stream of isochronous data packets [Fig. 3, 210].

However, Ghodrat does not teach regulating transmission of the stream of isochronous data packets as determined by the control instruction, wherein the control instruction instructs the transmitting device to stop transmitting the stream of isochronous data packets.

Dejanovic teaches regulating transmission of the stream of isochronous data packets as determined by the control instruction, wherein the control instruction instructs the transmitting device to stop transmitting the stream of isochronous data packets [Col. 9, lines 40-42, 58-64].

It would have been obvious to one of ordinary skill in the art at the time the invention was made to stop transmitting data packets if congestion occurs [Col. 9, lines 40-42].

**Regarding claim 32**, Ghodrat teaches an apparatus for communicating flow control and retransmission information [Fig. 1] comprising: a. a configuring circuit to configure a plug to communicate an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. a packetizing circuit to packetize flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; c. a transceiver circuit configured to communicate the isochronous back channel packet via the plug [Fig. 1, 25]; d. a de-packetizing circuit to extract the flow control and retransmission information from the

isochronous back channel packet [Col. 7, lines 43-49]; and e. a controller coupled to the configuring circuit, the packetizing circuit, the transceiver circuit, and the de-packetizing circuit to determine a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and apply the control instruction to the determined stream of isochronous data packet [Col. 7, lines 65-67 – Col. 8, lines 1-9].

However, Ghodrat does not teach the control instruction is an indication to stop transmitting the stream of isochronous data packets.

Dejanovic teaches the control instruction is an indication to stop transmitting the stream of isochronous data packets [Col. 9, lines 40-42, 58-64].

It would have been obvious to one of ordinary skill in the art at the time the invention was made to stop transmitting data packets if congestion occurs [Col. 9, lines 40-42].

Regarding claims 39 & 40, 48 & 49, Ghodrat teaches the transceiver circuit is configured to receive and transmit isochronous data packets in non real-time via the plug [Fig. 1, 25 transmits and receives, Col. 5, lines 40-41, asynchronous communication is not done in real-time].

Regarding claim 41, Ghodrat teaches an apparatus for communicating flow control and retransmission information [Fig. 1] comprising: a. means for configuring a plug to communicate an isochronous back channel packet over an isochronous back channel [Col. 5, lines 33-39]; b. means for packetizing flow control and retransmission information within the isochronous back channel packet [Col. 5, lines 61-63]; c. means for communicating the isochronous back channel packet via the plug [Fig. 1, 25]; d. means for extracting the flow control and retransmission

Art Unit: 2616

information from the isochronous back channel packet [Col. 7, lines 43-49]; and e. means for controlling coupled to the means for configuring, the means for packetizing, the means for communicating, and the means for de-packetizing, wherein the means for controlling determines a control instruction and a stream of isochronous data packets to which the control instruction is applied from the flow control and retransmission information and applies the control instruction to the determined stream of isochronous data packets [Col. 7, lines 65-67 – Col. 8, lines 1-9].

However, Ghodrat does not teach the control instruction is an indication to stop transmitting the stream of isochronous data packets.

Dejanovic teaches the control instruction is an indication to stop transmitting the stream of isochronous data packets [Col. 9, lines 40-42, 58-64].

It would have been obvious to one of ordinary skill in the art at the time the invention was made to stop transmitting data packets if congestion occurs [Col. 9, lines 40-42].

### ***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Chandrahas Patel whose telephone number is 571-270-1211. The examiner can normally be reached on Monday through Thursday 7:30 to 17:00 EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Ricky Ngo can be reached on 571-272-3139. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2616

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

CBP



RICKY Q. NGO  
SUPERVISORY PATENT EXAMINER